

## Specification



Dualsky Xmotor CA2 Series	XM3530CA			
Item No.(商品编码)	55122	55123	55124	55324
Model - Turns(马达转速)	XM3530CA-10	XM3530CA-12	XM3530CA-14	XM3530CA-16
RPM/V(KV)(KV值)	1430	1200	1000	920
Stator Diameter(定子直径)	28	28	28	28
Magnet length(磁铁长度)	8	8	8	8
Shaft diameter(轴径)	4	4	4	4
Mountingholes pitch(安装孔距)	19/25	19/25	19/25	19/25
Weight(g)(重量)	74	74	74	74
Resistance(Ri)(mOhm)(电阻)	49	75	102	113
Idle Current(Io) @10V (A)(空载电流)	1.42	1.01	0.75	0.68
No.of Cells(LiPo)(电池节数)	2..3	2..3	2..3	2..4
Max. EfficiencyCurrent[A](效率电流)	16	15	14	13
Max. Burst Current (15s)[A](最大电流)	28	26	24	24
Max. Power(15s)(最大功率)	250W	250W	250W	
Input Connectors[mm](金插)	DB3	DB3	DB3	DB3
Recommended ESC(推荐调速器)	XC2512BA	XC2512BA	XC2512BA	XC2512BA
Prop. Range(螺旋桨)	7x5...9x5	8x5...12x6	8x5...12x6	8x5...12x6
App. Class(适用机种)	480 size.10 Class			